

8723_{eQ} PE

8723_{eQ} PE SWA



Generally, to Belden 8723, RS232, UL1581



Application

22 AWG/ 7/0.254)

Individual screened pair Computer, Point of sale RS232 Cable. SWA option suitable for direct burial.

Construction

Conductor	Class 2 stranded tinned copper conductor
Inner Sheath	PE (polyethylene)
Pairs	2
Screen	Aluminium polyester foil
Drain Wire	Tinned copper
Inner sheath	PE (polyethylene) (Duct grade no armour for 8723eQ PE)
Armour	SWA (Steel Wire Armour)
Sheath	PE (Polyethylene Duct grade)
Nominal OD	8mm
Nominal Weight	210kg/km
Voltage Rating	300V
Temperature Rating	Fixed: -20°C to +80°C

Core Identification

Pair 1: Black / Red

Pair 2: Green / White

Sheath colour Black

This product is available in:

LSF – Low smoke

LSZH – Low Smoke Zero Halogen

Capacitance at 1kHz	Max Resistance of Conductor
pF/m	Ohms/km
114.8	60.5

The information contained within this data sheet is for guidance only.

Cable and gland sizes are nominal and may vary according to different manufacturer's tolerances.

Every possible effort is made to ensure that the Information contained in this data sheet is correct.

However, we reserve the right to change the information or specification at any time in the light of technical developments or revisions. References to or extracts from British Standards, current IEE regulations or other regulatory bodies should be verified with these organisations.

sales@premiercables.com

www.premiercables.com

WORLDWIDE CABLE SOLUTIONS