

8771eQ

8771eQ LSF

Coming Soon



Generally, to Belden 8771, UI style 2093



Application

22awg screened cable for data and audio applications where protection against electrical interference is needed.

Construction

Conductor	Class 2 stranded tinned copper conductor
AWG	22(7)
Cores	3
Core Identification	Red / Black /Transparent
Insulation	PE Polyethylene
Screen	Aluminium foil
Drain Wire	Tinned copper
Sheath	PVC or LSF (Low Smoke & Fume)
Voltage	600v
Temperature Rating	Fixed: -20°C to +80°C
Sheath Colour	Grey
Nominal O/D mm	5.05
Nominal weight kg/km	32

Capacitance conductor to conductor pF/m	Capacitance conductor to shield pF/m	Max Resistance of Conductor Ohms/km
75.46	134.52	49.21

The information contained within this data sheet is for guidance only.

Cable and gland sizes are nominal and may vary according to different manufacturer's tolerances.

Every possible effort is made to ensure that the Information contained in this data sheet is correct.

However, we reserve the right to change the information or specification at any time in the light of technical developments or revisions.

References to or extracts from British Standards, current IEE regulations or other regulatory bodies should be verified with these organisations.

sales@premiercables.com

www.premiercables.com

WORLDWIDE CABLE SOLUTIONS