

8777eQ

8777eQ LSF



Generally, to Belden 8774, RS232, UL 1581



Application

22awg multi-pair rated screened cable for RS232 applications.

Construction

Conductor	Class 2 stranded tinned copper conductor
AWG	22(7)
pairs	3
Insulation	PE (Polyethylene)
Screen	Aluminium foil
Drain Wire	Tinned copper
Sheath	PVC or LSF(Low Smoke & Fume)
Voltage	300v
Temperature Rating	Fixed: -20°C to +80°C
Sheath Colour	Grey
Nominal O/D mm	5.8
Nominal weight kg/km	68

Core Identification

Pair 1 Black/Red
Pair 2 Black/White
Pair 3 Black/Green

Capacitance at 1kHz	Max Resistance of Conductor
pF/m	Ohms/km
98.4	60.2

The information contained within this data sheet is for guidance only.
Cable and gland sizes are nominal and may vary according to different manufacturer's tolerances.
Every possible effort is made to ensure that the Information contained in this data sheet is correct.
However, we reserve the right to change the information or specification at any time in the light of technical developments or revisions.
References to or extracts from British Standards, current IEE regulations or other regulatory bodies should be verified with these organisations.

sales@premiercables.com
www.premiercables.com

WORLDWIDE CABLE SOLUTIONS