

9207_{eQ}

9207_{eQ} LSF



Generally, to Belden 9207



Application

Building management system cable.

Construction

Conductor	1 x class 5 Tinned copper / 1 x class 5 bare copper
Inner Sheath	PE (Polyethylene)
Pairs	1
Screen	Aluminium polyester foil
Drain Wire	Tinned copper
Screen	TCWB (Tinned Copper Wire Braid)
Sheath	PVC or LSF (Low Smoke & Fume)
Voltage	300v
Nominal O/D	9.1mm
Min Bending Radius	15x O/D flexing
Weight	89kg/km
Temperature Rating	Fixed: -20°C to +60°C
Core Identification	Pair 1: Transparent / Transparent
Sheath colour	white

Capacitance at 1kHz	Max resistance of Conductor at 20°C
pF/m	Ohms/km
47.5	36.7

The information contained within this data sheet is for guidance only.

Cable and gland sizes are nominal and may vary according to different manufacturer's tolerances.

Every possible effort is made to ensure that the Information contained in this data sheet is correct.

However, we reserve the right to change the information or specification at any time in the light of technical developments or revisions.

References to or extracts from British Standards, current IEE regulations or other regulatory bodies should be verified with these organisations.

sales@premiercables.com

www.premiercables.com

WORLDWIDE CABLE SOLUTIONS