

318-Y / H05VV-F EN 50525-2-11 Flexible Cable



Application

Ordinary duty PVC cable for use in domestic appliances, kitchens and offices. For use with light portable appliances such as table lamps and office equipment. Generally unsuitable for outdoor use or industrial applications.

Standards

EN 50525-2-11

EN 60228

Flame Retardant according to IEC/EN 60332-1-2

Characteristics

Voltage Rating U_o/U
300/500V

Temperature Rating
Flexed: +5°C to +70°C

Minimum Bending Radius
Flexed: 8 x overall diameter



Construction

Conductor

Class 5 flexible copper conductor

Insulation

PVC (Polyvinyl Chloride)

Sheath

PVC (Polyvinyl Chloride)

Sheath Colour

Black or White



Dimensions

NO. OF CORES	NOMINAL CROSS SECTIONAL AREA mm ²	NOMINAL THICKNESS OF INSULATION mm	NOMINAL OVERALL DIAMETER mm	NOMINAL WEIGHT kg/km
2	0.75	0.6	6.3	57
2	1	0.6	6.6	65
2	1.5	0.7	7.4	84
2	2.5	0.8	9.1	130
3	0.75	0.6	6.7	68
3	1	0.6	7	78
3	1.5	0.7	8.1	108
3	2.5	0.8	9.9	163
3	4	0.8	11.3	227
4	0.75	0.6	7.3	82
4	1	0.6	7.9	100
4	1.5	0.7	9	134
4	2.5	0.8	10.8	201
5	0.75	0.6	8.1	102
5	1	0.6	8.6	120
5	1.5	0.7	10	166

Conductors

Class 5 Flexible Copper Conductors for Single Core and Multi-Core Cables

NOMINAL CROSS SECTIONAL AREA mm ²	MAXIMUM DIAMETER OF WIRES IN CONDUCTOR mm	MAXIMUM RESISTANCE OF CONDUCTOR AT 20°C ohms/km
		Plain Wires
0.75	0.21	26
1	0.21	19.5
1.5	0.26	13.3
2.5	0.26	7.98
4	0.31	4.95

The above table is in accordance with EN 60228

Electrical Characteristics

Current Carrying Capacity and Mass Supportable

NOMINAL CROSS SECTIONAL AREA mm ²	CURRENT CARRYING CAPACITY Amps		MAXIMUM MASS SUPPORTABLE BY TWIN FLEXIBLE CORD (See regulations 522.7.2 and 559.6.1.5 of the 17th Edition of IEE Wiring Regulations) kg
	Single-Phase AC	Three-Phase AC	
0.75	6	6	3
1	10	10	5
1.5	16	16	5
2.5	25	20	5
4	32	25	5

The above table is in accordance with Table 4F3A of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52.

Voltage Drop

NOMINAL CROSS SECTIONAL AREA mm ²	DC OR SINGLE-PHASE AC mV/A/m	THREE-PHASE AC mV/A/m
0.75	62	54
1	46	40
1.5	32	27
2.5	19	16
4	12	10

Conductor operating temperature: 60°C*

The above table is in accordance with Table 4F3B of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52.

De-Rating Factors

De-Rating Factor for Ambient Temperature 60°C Thermoplastic or Thermosetting Insulated Cords

AIR TEMPERATURE	35°C	40°C	45°C	50°C	55°C
DE-RATING FACTOR	0.91	0.82	0.71	0.58	0.41

The above table is in accordance with Table 4F3A of the 18th Edition of IEE Wiring Regulations BS7671 and IEC 60364-5-52.

The information contained within this datasheet is for guidance only and is subject to change without notice or liability. All the information is provided in good faith and is believed to be correct at the time of publication. When selecting cable accessories, please note that actual cable dimensions may vary due to manufacturing tolerances.